

PRODUCTION COUNTER

A100-V1

RLY 1 RLY 2 SEN 1 SEN 2 SEN 3 SEN 3 SEN 5 SEN 5 C LENGTH / MONTOS O SPEED / DISLINGING PARTIE O TIPL / TIPLS O RUNTIME / BOOKSTREE O TIME / BOOK A 100 - V1

TEXPRO - 5A



FEATURES

- Suitable for Blow room, Carding, Drawing, Comber, Simplex, Spinning, TFO Machines etc..
- Displays: Length Delivered, Delivery Rate, TPI and TPM, Speed, Doff, Hanks, downtime and Runtime.
- Preset and Final set facility.
- TPI Monitoring and Alarm.
- Automatic shift Changeover.
- Programmable at site for all machines.
- Password protection.
- Communication facility with Computer.





FEATURES

- Suitable for Blow room, Carding, Drawing, Comber, Simplex, Spinning, Machines, etc.,
- Displays: Length Delivered, Delivery Rate, TPI / TPM, Speed, Hanks, Doff, Runtime.
- Preset and Final set facility.
- Password protection.

TECHNICAL SPECIFICATIONS			
	A100 - V2	A100 - V1	TEXPRO - 5A
Auxiliary power supply	85V - 250V AC	220V AC	220V AC
No. of Shifts	3 (Maximum)	3 (Maximum)	3 (Maximum)
Proxmity Sensor	NPN - NO Type	NPN - NO Type	NPN - NO Type
Dimension	145mm x 85mm (H)	120mm x 84mm (H)	96mm x 96mm (H)

OTHER PRODUCTS

- Inverter Drive for Spinning
- Speed controller for spinning machine
- Electronic Ribbon Breaker
- Maximum Demand Controller
- Power Meter
- Power Factor Controller
- Ammeter
- Voltmeter



INDUS ELECTRONICS INDIA (P) LTD

Plot No. 3, Electronics Industrial Estate, Civil Aerodrome Post, Coimbatore - 641 014. INDIA.

Ph : 91 - 422 - 2626020, 2628351, 2628508 E-mail : info@induselect.com, sales@induselect.com Web : www.induselect.com